

# Material Safety Data Sheet (GB)

according to 91/155/EEC



**Product name :** LUBA-print 121/F (ND)  
10% in Solventnaphtha/1-Methoxy-2-propylacetat  
**Revision :** 24.04.2007 **Version :** 3.0.0  
**Print date :** 25.04.2007

## 01. Identification of substance, preparation and company

**Product name :** LUBA-print 121/F (ND)  
10% in Solventnaphtha/1-Methoxy-2-propylacetat  
**Use of the substance / preparation :** Waxadditiv for lacquers and printing-inks.  
**Manufacturer/Supplier :** L. P. Bader & Co. GmbH  
**Street/P.O.Box :** Neckartal 140  
**Country code/Postal code/Town/City :** 78628 Rottweil  
**Telephone :** +49 741 / 9 42 52-0  
**Telefax :** +49 741 / 9 42 52-50  
**Emergency information :** +49 741 / 9 42 52-0

## 02. Composition/information on ingredients

### Chemical characterization

Waxdispersion

### Hazardous components

2-METHOXY-1-METHYLETHYL ACETATE ; EC-No. : 203-603-9 ; CAS-No. : 108-65-6

Percentage : 59,91 %

Classification : R 10 Xi ; R 36

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. ; EC-No. : 265-198-5 ; CAS-No. : 64742-94-5

Percentage : 26,49 %

Classification : N ; R 51/53 Xn ; R 65 R 67 R 66

1,2,4-TRIMETHYLBENZENE ; EC-No. : 202-436-9 ; CAS-No. : 95-63-6

Percentage : 3,01 %

Classification : R 10 N ; R 51/53 Xn ; R 20 Xi ; R 36/37/38

MESITYLENE ; EC-No. : 203-604-4 ; CAS-No. : 108-67-8

Percentage : 0,3 %

Classification : R 10 N ; R 51/53 Xi ; R 37

NAPHTHALENE ; EC-No. : 202-049-5 ; CAS-No. : 91-20-3

Percentage : 0,3 %

Classification : N ; R 50/53 Carc. Cat.3 ; R 40 Xn ; R 22

For the wording of the listed risk phrases refer to section 16.

## 03. Hazards identification

### Hazard designation

Flammable. · Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. · Irritating to eyes. · Vapours may cause drowsiness and dizziness.

Classification : R 10 · N ; R 51/53 · Xi ; R 36 · R 67 · R 66

## 04. First-aid measures

### General

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

### After inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

### After skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

### After eye contact

# Material Safety Data Sheet (GB)

according to 91/155/EEC



**Product name :** LUBA-print 121/F (ND)  
10% in Solventnaphtha/1-Methoxy-2-propylacetat  
**Revision :** 24.04.2007 **Version :** 3.0.0  
**Print date :** 25.04.2007

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

## **After ingestion**

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

## **Notes to a physician**

Symptomatic treatment. Give water with activated carbon for reducing absorption in the alimentary canal. Consider danger of aspiration into the lung..

## **05. Fire-fighting measures**

### **Suitable extinguishing media**

Foam, CO<sub>2</sub>, powder extinguisher.

### **Unsuitable extinguishing media**

Water.

### **Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

### **Special protective equipment**

Appropriate breathing apparatus may be required.

### **Additional information**

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

## **06. Accidental release measures**

### **Personal precautions**

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

### **Environmental precautions**

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

### **Methods for cleaning up/collecting**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

## **07. Handling and storage**

### **Information for safe handling**

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws.

### **Information about protection against explosions and fires**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### **Requirements to be met by storerooms and containers**

Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### **Information about separation of incompatible products**

Keep away from ignition sources - No smoking. Provide for sufficient ventilation. Do not store together with oxidants.

### **Further information about storage conditions**

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from ignition sources - No smoking.

# Material Safety Data Sheet (GB)

according to 91/155/EEC



**Product name :** LUBA-print 121/F (ND)  
10% in Solventnaphtha/1-Methoxy-2-propylacetat  
**Revision :** 24.04.2007 **Version :** 3.0.0  
**Print date :** 25.04.2007

**Storage class (VCI) :** 3A

## 08. Exposure controls and personal protection

### Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

### Components with critical values that require monitoring at the workplace (exposure limits)

2-METHOXY-1-METHYLETHYL ACETATE ; CAS-No. : 108-65-6

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace ( D )  
Value : 50 ppm / 270 mg/m<sup>3</sup>  
Category : 1(I)  
Remarks : Y  
Version date : 01.01.2006

Specification : Short term exposure limit ( EC )  
Value : 100 ppm / 550 mg/m<sup>3</sup>  
Remarks : H  
Version date : 08.06.2000

Specification : threshold limit value ( EC )  
Value : 50 ppm / 275 mg/m<sup>3</sup>  
Remarks : H  
Version date : 08.06.2000

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. ; CAS-No. : 64742-94-5

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace ( D )  
Value : 50 ppm / 200 mg/m<sup>3</sup>  
Version date : 23.07.2001

1,2,4-TRIMETHYLBENZENE ; CAS-No. : 95-63-6

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace ( D )  
Value : 20 ppm / 100 mg/m<sup>3</sup>  
Category : 2(II)  
Remarks : Y  
Version date : 01.01.2006

Specification : threshold limit value ( EC )  
Value : 20 ppm / 100 mg/m<sup>3</sup>  
Version date : 08.06.2000

MESITYLENE ; CAS-No. : 108-67-8

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace ( D )  
Value : 20 ppm / 100 mg/m<sup>3</sup>  
Category : 2(II)  
Remarks : Y  
Version date : 01.01.2006

### Personal protective equipment

#### General protective and hygiene measures

Wash hands before breaks and after work.

#### Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

#### Hand protection

Solvent-resistant protective gloves must be worn. After washing hands replace lost skin fat by fat containing skin creams. The glove material must be impermeable and resistant against the product/substance/preparation. Please observe manufacturer's instructions with regard to permeability and breakthrough time, as well as the particular conditions at the workplace

# Material Safety Data Sheet (GB)

according to 91/155/EEC



**Product name :** LUBA-print 121/F (ND)  
10% in Solventnaphtha/1-Methoxy-2-propylacetat  
**Revision :** 24.04.2007 **Version :** 3.0.0  
**Print date :** 25.04.2007

(mechanical stress, duration of contact). Recommended materials (please observe manufacturer's instructions): Nitrile rubber gloves. Butyl rubber gloves. Fluorocarbon rubber gloves.

## Eye protection

Use safety glasses.

## Body protection

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

## 09. Physical and chemical properties

### Image

**Form :** Liquid.  
**Colour :** White.  
**Odour :** Characteristic.

### Relevant safety data

<b>Boiling point / range :</b>	( 1013 hPa )	ca.	146 °C	literature
<b>Flash point :</b>			45 °C	ASTM D 6450
<b>Ignition temperature :</b>		ca.	315 °C	literature
<b>Lower explosion limit :</b>			0,8 % b.v.	literature
<b>Upper explosion limit :</b>			10,8 % b.v.	literature
<b>Vapour pressure :</b>	( 50 °C )		22 hPa	literature
<b>Density :</b>	( 20 °C )	ca.	0,93 g/cm <sup>3</sup>	DIN 53217
<b>Solvent-separation test :</b>	( 20 °C )	<	3 %	
<b>Solubility in water :</b>	( 20 °C )		insoluble	
<b>Viscosity :</b>	( 23 °C / at 1291 s-1 )	ca.	16 mPa.s	DIN 53214
<b>Content VOC (EC) :</b>			90,3 % b.w.	

## 10. Stability and reactivity

### Conditions to avoid

Stable under recommended storage and handling conditions(See section 7). Keep away from oxidizing agents

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## 11. Toxicological information

### Experience on practice

Inhalation/eye contact: in high concentrations irritating to the mucous membranes, narcotic effect and influence on power of reaction and loss of coordination possible. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea. In case of contact with the product: danger of resorption through the skin, irritation of skin/mucous membranes. Eye contact: irritation. In case of swallowing: even minor quantities may lead to considerable damage to health.

### Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

## 12. Ecological information

### Additional ecological information

Do not empty into waters or drains.

## 13. Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium. Always observe official regulations. EAK-waste-code: 070 704

# Material Safety Data Sheet (GB)

according to 91/155/EEC



**Product name :** LUBA-print 121/F (ND)  
10% in Solventnaphtha/1-Methoxy-2-propylacetat  
**Revision :** 24.04.2007 **Version :** 3.0.0  
**Print date :** 25.04.2007

## 14. Transport information

### Land transport ADR/RID

#### Classification

**Class :** 3 **Kemlercode :** 30  
**Substance number :** 1993 **Classification-Code :** F1  
Special provisions : 640E · LQ 7 · Tunnel restriction code : E

#### Proper shipping name

FLAMMABLE LIQUID, N.O.S.

#### Hazardous components

2-METHOXY-1-METHYLETHYL ACETATE · 1,2,4-TRIMETHYLBENZENE

#### Packaging

**Packaging group :** III  
**Label :** 3

### Maritime transport IMDG/GGVSea

#### Classification

**IMDG-Code :** 3 **EmS number :** F-E / S-E  
**UN number :** 1993 **Marine Poll. :** P  
LQ 5 I

#### Proper shipping name

FLAMMABLE LIQUID, N.O.S.

#### Hazardous components

2-METHOXY-1-METHYLETHYL ACETATE · SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. · 1,2,4-TRIMETHYLBENZENE

#### Packaging

**Packaging group :** III  
**Label :** 3

### Air transport ICAO-TI and IATA-DGR

#### Classification

**Class :** 3  
**UN number :** 1993

#### Proper shipping name

FLAMMABLE LIQUID, N.O.S.

#### Hazardous components

2-METHOXY-1-METHYLETHYL ACETATE · 1,2,4-TRIMETHYLBENZENE

#### Packaging

**Packaging group :** III  
**Label :** 3

## 15. Regulatory information

### Classification according to EC directives

#### Danger symbol and danger designation



Xi ; Irritant



N ; Dangerous for the environment

#### R-phrases

10 Flammable.  
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# Material Safety Data Sheet (GB)

according to 91/155/EEC



**Product name :** LUBA-print 121/F (ND)  
10% in Solventnaphtha/1-Methoxy-2-propylacetat  
**Revision :** 24.04.2007 **Version :** 3.0.0  
**Print date :** 25.04.2007

36 Irritating to eyes.  
67 Vapours may cause drowsiness and dizziness.  
66 Repeated exposure may cause skin dryness or cracking.

#### S-phrases

57 Use appropriate container to avoid environmental contamination.  
61 Avoid release to the environment. Refer to special instructions/Safety data sheets.  
51 Use only in well-ventilated areas.  
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
24/25 Avoid contact with skin and eyes.

#### National regulatory information

##### Emission control act ("TA-Luft")

Sum organic substances class I : < 5 %

##### Water pollution classification

Class : 2 according VwVwS

## 16. Other information

### Further information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

#### Relevant changes

02. Hazardous components · 08. Components with critical values that require monitoring at the workplace (exposure limits) · 14. Classification (ADR) · 14. Proper shipping name (ADR) · 14. Substance releasing the danger (ADR) · 14. Proper shipping name (IMDG) · 14. Substance releasing the danger (IMDG) · 14. Proper shipping name (ICAO) · 14. Substance releasing the danger (ICAO) · 15. Emission control act ("TA-Luft")

#### R-Phrases of components

10 Flammable.  
20 Harmful by inhalation.  
22 Harmful if swallowed.  
36 Irritating to eyes.  
36/37/38 Irritating to eyes, respiratory system and skin.  
37 Irritating to respiratory system.  
40 Limited evidence of a carcinogenic effect.  
50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
65 Harmful: may cause lung damage if swallowed.  
66 Repeated exposure may cause skin dryness or cracking.  
67 Vapours may cause drowsiness and dizziness.

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.