

L.P. Bader & Co. GmbH  
 Neckartal 140 D-78628 Rottweil  
 ☒ Postfach 1137 D-78611 Rottweil

Telefon: + 49 (0)7 41-9 42 52-0  
 Telefax: + 49 (0)7 41-9 42 52-50

E-Mail: [service@lubaprint.de](mailto:service@lubaprint.de)  
 Internet: [www.lubaprint.de](http://www.lubaprint.de)

## LUBA-print Wax Dispersion VP 967/A

### Application field:

Water based care product for parquet floors with antislip and matting effects.

### Processing information:

For first use apply undiluted. The first application should be applied in a thin film. The subsequent polishing results in a semi gloss film and a good sealing and antislip.

For further caring, the product should be added into the water.  
 50 - 100 ml of this care product to be added to 5 Ltr. water.

### Technical data:

### Unit:

### Method:

Solid:	min:	11,0 %	Sartorius MA 100 infrared drier
	max:	13,0 %	
Solvent:		Wax compound	
		Water	
Emulsifier-system:		non - ionic / anionic	
pH-Value:	min:	8,0	DIN ISO 976
	max:	9,0	
Density:	min:	0,99 g/ccm	Pyknometer DIN EN ISO 2811-1
	max:	1,01 g/ccm	
Viscosity:	typ.:	80 mPa.s	Rheolab MC1 DIN 53019 1.291s-1

Experimental product: Temporary data, final limits can be given after 5 produced batches.

### Storage:

In original closed containers lasting at least 12 months at temperatures between 5-35°C.

Stir well before use!

Protect from frost!

After long storage, particularly after usage of some of the product, evaporation of water is possible and visible signs of particles may be present.

We therefore recommend filtration of the product before use.

The above mentioned information is derived from our quality checks. It does not relieve the purchaser from examining the product delivery and gives no assurance of suitability of the product for any particular purpose.